

# DP991

## Detector analógico óptico. Serie 990.

### General

---

The DP991 is an elegant, slim-line, optical sensor with high performance analogue addressable features. Compensation for sensor drift is included as part of the internal signal-processing algorithm.

### Optical Smoke Monitor

---

The optical smoke detectors has an internal pulsing LED and a photo-diode at an obtuse angle. In clear air conditions the photo-diode in the monitor receives no light from the LED and produces a corresponding analogue signal. This signal increases when smoke enters the chamber and light is scattered onto the photodiode. The signal is processed by the electronic circuitry and transmitted to the control equipment in exactly the same way as in the case of the ionisation smoke monitor.

### Drift Compensation

---

The drift compensation algorithm will compensate for changes in sensor output caused, for example, by dust in the chamber, and will therefore hold the sensitivity at a constant level even with severe chamber contamination. This increased stability is achieved without significantly affecting the detector's sensitivity to fire.

Compensation values are stored in nonvolatile memory and will be retained even if detectors are disconnected.

### Unique Addressing

---

A unique, patented addressing method provides simple, user-friendly and accurate identification of monitor location whereby a coded card, inserted in the base, is read by any monitor as it is plugged in. All the electronic components are in the monitor, but the location information is held in the base. Addressing errors during maintenance and service are eliminated. Precoded and pre-numbered address cards are also available. These address cards simplify and speed up installation and commissioning.



### Details

---

- 5 Approved response modes for ease of optimisation to different environments
- Rejection of transient signals
- Drift compensation to ensure constant sensitivity
- 360° Alarm visibility
- Flashing LED option
- Fast alarm reporting
- EN54 approved and CPR certified

# DP991

## Detector analógico óptico. Serie 990.

### Technical specifications

---

#### General

---

Indicación de estado	2 clear LEDs (red in alarm)
----------------------	-----------------------------

---

#### Eléctrico

---

Voltaje de funcionamiento	17 to 28 VDC
---------------------------	--------------

---

Voltaje de comunicación	5 - 9 V (peak to peak)
-------------------------	------------------------

---

Consumo de corriente	300 $\mu$ A (quiescent) 3.5 mA (alarm)
----------------------	---

---

#### Salida

---

Ratio y tipo de salida	Remote LED output (< 5 mA)
------------------------	----------------------------

---

#### Físico

---

Dimensiones físicas	100 x 42 mm (Ø x H)
---------------------	---------------------

---

Peso neto	105 g
-----------	-------

---

Color	Blanco
-------	--------

---

Material	Policarbonato
----------	---------------

---

#### Medioambiental

---

Temperatura de funcionamiento	-20 to +60°C
-------------------------------	--------------

---

Temperatura de almacenamiento	-40 to +70°C
-------------------------------	--------------

---

Humedad relativa	0 to 95% noncondensing
------------------	------------------------

---

Entorno	Interior
---------	----------

---

Clasificación IP	IP44
------------------	------

---

#### Estándares y regulaciones

---

Certificación	EN54-7
---------------	--------

---

#### Environmental

---

Max. wind (continuous)	Not affected
------------------------	--------------

---



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de [es.firesecurityproducts.com](http://es.firesecurityproducts.com) o póngase en contacto con su comercial.

Last updated on 8 December 2021 - 11:44