

DS-PWA64/96 AX PRO

AX PRO supports Wi-Fi, TCP/IP, and GPRS/3G/4G communication methods. It also supports Hik-ProConnect, Hik-Connect, Hik IP Receiver, Hik IP Receiver Pro and Hik-Central, which is applicable to the scenarios of market, store, house, factory, warehouse, office, etc.



Key Feature

- TCP/IP, Wi-Fi, and GPRS/3G/4G network
- New generation wireless protocol: Tri-X/Cam-X
- Long RF transmission distance
- Two-way communication with AES-128 encryption
- Connects up to 96 wireless zones/outputs (including 48 PIRCAMs), 48 wireless keyfobs, 4 repeaters, 6 sounders, 8 tag readers & keypads.

The capability varies according to the model of device.

- Supports up to 48 network users, including 1 installer, 1 administrator, and 46 normal users
- Voice prompt
- Configuration via Web client, mobile client, and Convergence Cloud
- Hik-Connect and Hik-ProConnect configuration depends on the user access level
- Pushes alarm notification via messages or phone calls
- Views live videos from Hik-Connect
- Alarm video clips via emails and APP
- Uploads alarm reports to ARC
- Supports LED indicator to indicates system status
- 4520 mAh lithium backup battery
- SIA-DC09 protocol, and supports both Contact ID and SIA data format
- Supports Hik-IP Receiver and Hik-IP Receiver Pro for ARC communication

Available Model

- DS-PWA96-M-WE
- DS-PWA64-L-WE



Specification

| | | AX PRO L | AX PRO M |
|-----------------------|-----------------------------------|--|---|
| Basic | Frequency | 868Mhz | |
| | Wireless type | 2-way wireless | |
| | Wireless Security | Frequency Hoping 128 AES Encryption | |
| | Wireless Zones | Up to 64 | Up to 96 |
| | Wireless Outputs | (Up to 48 PIRCAMs) | (Up to 48 PIRCAMs) |
| | Wireless Tag Readers & Keypads | Up to 8 | |
| | Wireless Sounders | 4 | 6 |
| | Wireless Keyfobs | 32 | 48 |
| | Wireless Repeaters | 2 | 4 |
| | Tags | 32 | 48 |
| | PIRCAM | Supported | |
| | Onboard IP CAMERA Integration | 0 | 4*7s clips 4 clips have their own storage, not overrides each other |
| User | Installer | 1 | |
| | Admin | 1 | |
| | Users | 30 | 46 |
| Key Software Features | Areas | 16 | 32 |
| | Voice prompt | Supported | |
| | Loudspeaker built in | Supported | |
| | Tag reader built in | N/A | Supported |
| | LEDs Status | Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power | |
| | Memory Log stored | 5000 | |
| | RS-232 output | Supported | |
| | Programming tools | Hik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence Cloud | |
| | Firmware upgrade | APP Manual or Web | |
| | Arm Modes | Away/Stay | |
| | Automatic Arm/Disarm Timers | Supported | |
| | Forced Arming with Open Zones | Supported | |
| | Diagnostics of via the APP or Web | Supported | |
| Communication | LAN port | Supported | |
| | Wi-Fi on board | Supported(2.4G) | |
| | GPRS on board | Supported | N/A |
| | 3/4G on board | N/A | Supported |

| | | | |
|------------|--|---|------|
| | SIM slot | Single | Dual |
| | SMS notification | Supported | |
| | Alarm voice call | Supported | |
| | ARC protocol | SIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK) Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote control | |
| | User APP for operating | Supported | |
| | Installer APP for programming | Supported | |
| | Web server for maintenance (offline configuration) | Supported | |
| Hardware | Battery Stand by | 12 hours | |
| | Power Supply | Built in power supply | |
| | Battery pack | Built in on board Battery Li | |
| | Housing | Plastic | |
| Automation | Schedules | Wall switch & Relay & Plug (Has time schedule) | |
| Approvals | EN | EN50131 Grade 2 | |
| | CE | Supported | |
| | Rohs/Reach/WEEE | Supported | |
| Others | Operation temperature | -10 °C to +55 °C | |
| | Dimension(W x H x D) | 170.0 mm (6.7") x 170.0 (6.7") mm x 38.6 mm (1.5") | |
| | Weight | 557.5 g(19.7 oz) | |

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com